



M900S Series™

900 MHz

Broadband Wireless System

The M900S Series point-to-multipoint wireless broadband platform utilizes the benefits of the 900 MHz license exempt spectrum and delivers up to 3 Mbps to the subscriber. Ideal for areas with foliage, the M900S is a fully integrated outdoor unit which includes an internal dual polarized antenna as well as a connector for an optional external antenna.

Product Highlights

- **900 MHz NON-LINE-OF-SIGHT PERFORMANCE**

The M900S was designed for deployment in areas where foliage obscures line-of-sight between the access point (AP) and subscriber unit (SU). The system offers excellent receiver sensitivity and provides a two-mile line-of-sight range using internal antennas with 30 dB fade margin as well as an outstanding non-line-of-sight (NLOS)* range. Use of external antennas increases range and fade margin even further.

- **ANTENNA FLEXIBILITY**

The M900S Series AP and SU both include an integrated 9 dBi dual polarized patch antenna as well as a connector for an optional external antenna. External antenna options include a 9 dBi omni antenna for the AP and a 15 dBi yagi for both the AP and SU. The user can select the internal or external antenna, or allow the firmware to choose the antenna with the strongest signal.

- **SPEED & RATE SHIFTING**

The M900S delivers up to 3 Mbps and features automatic rate shifting (to 1.5 Mbps) to accommodate operation of wireless links in less than ideal signal strength conditions. The M900S AP utilizes Trango's patent pending SmartPolling™ algorithm to dynamically and adaptively poll subscriber units, ensuring the lowest latency for active subscribers.

- **CHANNEL FLEXIBILITY**

The M900S is configured with four channels, each 6 MHz apart. The user can redefine channels by selecting frequencies in single MHz increments. The SU scans all channels until it associates with a properly configured AP. This allows redundancy of APs as well as a simple and quick method to switch channels on an entire sector.

- **INTERFERENCE MITIGATION**

The M900S offers powerful interference mitigation tools such as dual polarity antennas, automatic SU power leveling, and receive threshold control.

- **INTEGRATED DESIGN**

The M900S radios are fully weatherized outdoor units featuring Power-over-Ethernet (PoE) designed for quick deployment and easy installation.

- **MANAGEMENT FEATURES**

The M900S offers remote and local management via Telnet, SNMP and HTTP via browser. Powerful tools such as site survey and upstream/downstream CIR/MIR controls allow operators total control and flexibility in managing their network.

* Non-line-of-sight performance may vary due to leaf density, moisture content, and other environmental factors.

M900S Specifications

RADIO PARAMETERS

Frequency of Operation	902 - 928 MHz
Channels	4 non-overlapping, user changeable
Channel Spacing	6 MHz, user changeable
RF Power Output	+27 dBm Max Setting -8 dBm Min Setting
Modulation Format	Direct Sequence Spread Spectrum (DSSS)
Certification / Compliance	FCC Part 15.247
Receiver Sensitivity (BER 10 ⁻⁶)	-88 dBm in 3 Mbps mode and -91 dBm in 1.5 Mbps mode

DATA AND OPERATIONAL PARAMETERS

Access Method	TDD with SmartPolling™
User Data throughput	3 Mbps or 1.5 Mbps
Upstream/Downstream Throughput	Dynamic, automatically adjusts to suit demand
Bandwidth Control	CIR and MIR upstream/downstream control by AP
Maximum Number SUs per AP	126
Rate Shifting Feature	Automatic shift to lower rate based on packet errors. User can also set radio to either rate and disable rate shifting.
Security	Trango proprietary authentication method, based on MAC address and alphanumeric base ID; over-the-air data scrambling.
Configuration & Management	Telnet, SNMP, TFTP, HTTP

ANTENNA PARAMETERS

Internal Antenna (AP and SU)	Integrated 9 dBi 60°X60° patch dual polarized (HPOL/VPOL)
Omni Antenna (Optional)	9 dBi 360° X 10° with SMA RP Connector (VPOL)
Yagi Antenna (Optional)	15 dBi 30° X 30° with SMA RP Connector (VPOL or HPOL)

POWER PARAMETERS

Power Method	Power over Ethernet (PoE Injector JBox included)
Voltage Input	24 VDC
Standard Power Supply	120VAC to 24VDC
PoE Cat-5 Max Cable Length	300 feet on 24 AWG STP Cat-5 cable

PHYSICAL AND ENVIRONMENTAL

Ethernet Interface	RJ45, 10/100BaseT, auto sense, auto negotiate
Antenna Connector	SMA reverse polarity
Reset Button	Resets unit to factory default settings
Radio Enclosure	All-weather, powder coated, cast aluminum with polycarbonate radome
Temperature Range	-40° to 60° C (-40° to 140° F)
Radio Weight	4 lbs.
Radio Dimensions	12.5" x 8" x 2.75"
Standard Mounting Hardware	2 U-Brackets, all-thread, nuts and washers (for pole mount)
Shipping Weight	10 lbs. (without external antennas)

Features and Specifications are preliminary and subject to change without notice.