

TEWTOC



Insight D-225 Integrated Multi-Function DVR

Specification

Operation System	Microsoft Windows 2000 and above
Split Screen	4 · 9 · 16 · 25 Split Screen ; Can setup camera groups & auto switch
Video Input	IP Camera · Video Server · Regular CCTV Camera · 6th or D225 Point
Resolution	NTSC 640X480 · 320X240 PAL 704X576 · 352X288
Compression	M-JPEG
Monitoring Speed	Max. 30 fps per each split screen
Recording Speed	Max. 30 fps per each channel
Setting Mode	Can select each video input · recording frames · video quality · image size
Recording Mode	Continuous · Events · Programmed
Storage	Hard Disk · USB or 1394 interface external Hard Disc · Disk RAID · NAS System · Tape Storage
Video Search	Provide the perpetual calendar and different color mode for user searching history files
Motion Detection	Motion detection areas can be drag by user without limited and can be overlap for selected area
Motion Alarm Notice	When touch of the motion detection, D225 will send out the single photo via e-mail

PT SARANA TEKNOTELMAS Ph : 4506484 <http://www.saranatel.com> <http://www.saranatel.co.cc>

TEWTOC

File Transfer	Image files can be transfer into AVI file for playback.
File Backup	Auto(By schedule) or manual backup; can be remote backup
E-Map	Can show out location of D225 & cameras, click the camera then can show out real-time image of the camera
DVDO	Can connect to external DVDO controller
Auto Alarm Notice	When sensor been touch off, it will ticker on E-map to show the location and start on the alarm bell. E-map will auto switch to alarm location
Auto Recovery	D225 will auto recovery to original situation after power failure
Multi-function	Can be recoding - monitoring - playback at the same time
Network Capability	Can real-time monitoring and playback history file thru internet

Specification subject to changed without notice.