

# MAP-811E

## A member of the *MacroStack* Family

2.4GHz ISM Band DSSS 11Mbps Wireless Access Point

### Features

- Desktop Wireless Access Point for Indoor Application
- One 10Mbps 10BASE-T LAN port
- IEEE 802.11b compliant, 2.4GHz ISM band DSSS 11Mbps
- Wireless Transmission at 1/2/5.5/11Mbps Auto/Fixed Speed
- Supports SNMP, Utility Management
- Supports Hardware and Software AP Mode Configuration
- Wireless Roaming capability
- Easy Firmware Upgrade
- Supports Power Input from DC or UTP/STP Cable (optional accessory needed)
- Slim Design That Fits Anywhere
- Wall-mount, Desktop or Magnet Attachment Installation
- Plug and Play installation



### Technical Specifications

Ports	1 RJ-45 10Mbps LAN
LED Indicators	RX, LINK, WRX, WLINK, POWER
Frequencies	2.4 - 2.483GHz Spread Spectrum
Number of Channels	11 (IC, FCC), 13 (ETSI), 14(TELEC)
Wireless Data Rate	1, 2, 5.5, 11Mbps
Standards Compliance	IEEE 802.11b (11Mbps WLAN), IEEE 802.3 (10BASE-T)
Power Supply	DC 5.5-7.0V
Emission & Safety	CE, FCC Class B
Dimensions	81mm x 26.5mm x 175mm
Weight	200g
Operating Temperature	0C~55C, 5%-95% Humidity (non condensing)
Maximum RF Output Power	20mW
Desktop/Rack Mount	Desktop